


Technicale Data:
The technical data listed here are examples. All data correspond to the information from the planning guide for the car lift Pegasos. Further information can be found there.

Example Lift
Payload: 3.000 kg
Lifting speed: 0,15 m/s
Axel load: max. 1.650 kg
Cabin width: 2.800 mm
Cabin depth: 5.800 mm
Cabin height: 2.100 mm
Lifting height: 3.500 mm
Pit: 150 mm
Shaft width: 3.400 mm
Shaft depth: 5.860 mm
Head room: 2.550 mm
Number of stops: 2
Entrances: 2, through car loading
Control box: 1.000mm x 300mm x 2.100mm (WxDxH)
Shaft doors: Sliding doors

Thermal insulation can only be installed on site after the elevator system has been installed. Insulation is not possible in the area of the guide column attachment & cable duct & bracket.

Notice:
This sample shaft drawing of the PEGASOS® car lift serves only as information material and does not replace the official shaft drawing. An official shaft drawing of the elevator is required for the final and detailed building planning. If necessary and in consultation with you, our sales department and our construction team will adapt this to your building project.

COPYRIGHT & DISCLAIMER
The content of these drawing template particularly text and graphics are protected by copyright. Un- less indicated otherwise, copyright is held by Lödige Fördertechnik GmbH. The content of this document must not be published without the express consent of Lödige Fördertechnik GmbH. We reserve the right to make technical changes to the drawing template for the PEGASOS® car lift.

Car- & Passenger Lift PEGASOS after MD 2006/42/EC Payload: 3.000 kg Lifting speed 0,15 m/s				Shaft drawing template PEGASOS		<div>LÖDIGE Fördertechnik GmbH</div> <div>Udberg, Immostrasse, D-42699 Solingen Weyersberg-Strasse 10 Tel. +49 (0)212 2001-1 Fax +49 (0)212 2001-111 info@loedige.de</div>	Page No.: PEGASOS Drawing No.: TEMPLATE
Boards:		Date:	Name:	Scale:			
Copy:		27.03.2020	HAASE	1:20			